

TECHNICAL DETAILS

Design 13 RP (Wet area)

This type is TÜV-certified and has the GS mark (tested for safety).

Height

2030 mm with 150 mm ground clearance, headroom 1985 mm
2170 mm with 150 mm ground clearance, headroom 2125 mm

Front walls

13 mm water resistant HPL-Panels with coarse matt surface on both sides. All visible edges milled and bevelled. An aluminium cover rail, 45 x 86 mm, which runs over the entire front, guarantees high stability. In the area of the wall connections, this is provided with aluminium cover caps to achieve a clean finish. Wall connections with rounded aluminium-U-profiles 22 x 30 mm.

Doors

Same material as front walls, self closing.
All edges rounded off in 20 mm radius, all corners in 9 mm radius. Door stop with rounded aluminium profile \varnothing 45 mm. Rubber seal on lock side for silent closing.

Partitions

Same material as front walls.
All visible edges milled and bevelled. Wall and front connections with rounded aluminium-U-profiles 22 x 30 mm.

Support Legs

Powder-coated aluminium profiles, 40 mm diameter, with heavy-duty nylon rosettes, height-adjustable, concealed fixing to the floor, inserted into vertical profiles.

Hardware

Each door with 3 triple knuckle stainless steel hinges with brass axle, thereof one spring hinge. Either polished or powder-coated in 7 colours without surcharge. Delta-Tone and Delta-Seal coating protect the spring inside the hinge from corrosion.
Powder-coated aluminium lock case with stainless steel latch and turn button with red/white indicator with emergency opening on the outside.

Accessories

Each cubicle with 1 nylon coat hook and a door buffer.
Concealed fixing.

Profiles

Anodized or powder-coated, available in 7 colours without surcharge. Supports for privacy screens are available only powder coated.

Colours for panels

12 standard colours without surcharge and 18 special colours at extra cost.

Colours for nylon parts

7 colours available without surcharge.

Privacy Screens wall mounted

400 x 900 mm
Wall connection with four powder-coated support angles. Front corners with 100 mm radius.

13 mm version: same material as front walls.

Glass version: consisting of 2 pieces of glass with a matt foil in between.

Privacy Screens floor mounted

500 x 1850 mm
Same material as front walls.
Wall connection with four powder-coated support angles. Bottom of the screen fixed with support leg.

Environmental Protection

We do not use materials containing PVC or asbestos.

Suitable for high demands in wet areas.

