

TECHNICAL DETAILS

Design 30 FN (Wet area)

This type is TÜV-certified and has the GS mark (tested for safety).

Height

2015 mm with 150 mm ground clearance,
headroom 1995 mm
2155 mm with 150 mm ground clearance,
headroom 2135 mm

Front Walls

30 mm panels consisting of a 24 mm high-strength and water-resistant PU core with 3 mm HPL textured melamine resin on both sides. All visible edges with laser edgebanding. An aluminium top profile, 43 x 20 mm, covers the entire length of the front wall to give additional stability. In the area of the wall connections, this is provided with aluminium cover caps to achieve a clean finish. Wall connection with aluminium u-profiles, 33 x 30 mm. Pilaster panels with more than 100 mm width with support leg.

Doors

same material as front walls. All edges with laser edgebanding. All corners and edges radius 3 mm. Embedded aluminium doorstop profile, 21 x 17,5 mm. Rubber cushion on the lock side for silent closing.

Partitions

Same material as doors. All visible edges on top and bottom with laser edgebanding. Wall and front connection with aluminium u-profiles, 33 mm x 30 mm. Because of weight reasons partition walls are partly made of water resistant rigid foam.

Support Legs

Powder-coated aluminium profiles, 20 mm diameter, with heavy-duty nylon rosettes, height-adjustable, concealed fixing to the floor.

Hardware

Triple knuckle stainless steel hinges, either polished or powder-coated in 7 colours without surcharge. Nylon handle set (23 mm dia). Inside the cubicle rosette with olive button, outside red/white indicator with emergency opening. Mortice lock with latch and bolt, rounded 20 mm.

Accessories

Each cubicle with 1 nylon coat hook and a door buffer. Concealed fixing.

Profiles and support angles

Anodized or powder-coated, available in 7 colours without surcharge.

Colours for panels

12 standard colours without surcharge and 18 special colours at extra cost.

Colours for nylon parts

7 colours available without surcharge.

Privacy Screens wall mounted

400 x 900 mm:
Wall connection with four support angles.

30 mm version: same material as front walls.

Glass version: consisting of 2 pieces of glass with a matt foil in between.

Privacy Screens floor mounted

500 x 1850 mm:
Same material as front walls.
Wall connection with four support angles. Bottom of the screen fixed with support leg.

Environmental Protection

We do not use materials containing PVC or asbestos.

Suitable for wet areas.

