

## TECHNICAL DETAILS

### Design 30 RW (Dry area)

---

**This type is TÜV-certified and has the GS mark (tested for safety).**

Height: 2015 mm  
Ground clearance: 150 mm  
Headroom: 1995 mm  
or  
Height: 2155 mm  
Ground clearance: 150 mm  
Headroom: 2135 mm

#### Front Walls

30 mm chipboard faced with textured melamine resin on both sides. All visible edges with laser edgebanding. An aluminium top profile, 43 x 20 mm, covers the entire length of the front wall to give additional stability. In the area of the wall connections, this is provided with aluminium cover caps to achieve a clean finish. Wall connection with aluminium u-profiles, 33 x 30 mm. Pilaster panels with more than 100 mm width with additional support leg.

#### Doors

From same material as front walls. All edges with laser edgebanding. All corners and edges radius 3 mm. Aluminium doorstop profile, 38 x 18 mm, with rubber cushion on the lock side for silent closing.

#### Partitions

From same material as front walls. All visible edges on top and bottom with laser edgebanding. Wall and front connection with aluminium u-profiles, 33 mm x 30 mm.

#### Support Legs

Powder-coated aluminium profiles, 20 mm diameter, with heavy-duty nylon rosettes, height-adjustable, concealed fixing to the floor.

#### Hardware

Triple knuckle stainless steel hinges, either polished or powder-coated in 7 colours without surcharge. Nylon handle set (23 mm dia). Inside the cubicle rosette with olive button, outside red/white indicator with emergency opening. Mortice lock with latch and bolt, rounded 20 mm.

#### Accessories

Each cubicle with 1 nylon coat hook and a door buffer. Concealed fixing.

#### Profiles

Anodized or powder-coated, available in 7 colours without surcharge. Supports for privacy screens are available only powder-coated.

#### Colours for panels

12 standard colours without surcharge and 18 special colours at extra cost.

#### Colours for nylon parts

7 colours available without surcharge.

#### Privacy Screens wall mounted

400 x 900 mm:  
Wall connection with four powder-coated support angles.

**30 mm version:** from same material as front walls.

**Glass version:** consisting of 2 pieces of glass with a matt foil in between.

#### Privacy Screens floor mounted

500 x 1850 mm:  
Same material as front walls.  
Wall connection with four powder-coated support angles.  
Bottom of the screen fixed with support leg.

#### Environmental Protection

We do not use materials containing PVC or asbestos.

Suitable for dry areas.

