

## TECHNICAL DETAILS

### Kindergarten 30 KG (Dry area)

---

**This type is TÜV-certified and has the GS mark (tested for safety).**

#### Height

1400 mm with 89 mm ground clearance.

#### Front

Made of 30 mm chipboard coated with textured melamine resin on both sides. All visible edges seamlessly coated with laser edgeband. Wall connections at on-site wall with aluminium brackets and U-profiles.

#### Doors

Made of same material as front walls. All visible edges seamlessly coated with laser edgeband. All corners and edges are round. The door width is 470 mm, the passage width 474 mm.

According to regulations of the trade association the doors are equipped with finger trap protection on both sides.

#### Partitions

Made of same material as front walls. All visible edges seamlessly coated with laser edgeband. Connection to the front with solid double-sided aluminium brackets. Wall connections at on-site wall with aluminium brackets and U-profiles.

#### Support Legs

Powder-coated aluminium profiles, 20 mm diameter, with heavy-duty nylon rosettes, height-adjustable, concealed fixing. The support legs are inserted 50 mm into the panels.

#### Hardware

Each door with 2 triple knuckle stainless steel hinges with brass axle, thereof one spring hinge. Either polished or powder-coated in 7 colours without surcharge. Delta-Tone and Delta-Seal coating protect the spring inside the hinge from corrosion. Doors are self-closing. Circular handle and handle plate with buffer to avoid injuries.

#### Colours for profiles, hinges and brackets

Anodized or powder-coated in 7 colours without surcharge.

#### Colours for panels

12 standard colours without surcharge and 18 special colours at extra cost.

#### Colours for nylon parts

7 colours available without surcharge.

#### Environmental Protection

We do not use materials containing PVC or asbestos.

Suitable for normal use in dry areas.

