

TECHNICAL DETAILS

Lockers 19 TS (Dry area)

This type is TÜV-certified and has the GS mark (tested for safety).

Width

Wardrobes:

300 mm, 470 mm, 600 mm (not GS5)

Staff lockers:

400 mm, 470 mm, 600 mm

Height

1850 mm and 1500 mm plus plinth

Depth

530 mm

Other sizes are available on request.

Carcass

All components are made in 19 mm wall thickness, the rear walls in 10 mm thickness. The chipboards are textured with melamine resin on both sides. They are highly resistant to impact, abrasion and scratching. The visible panels and edges are available in all decors, all non-visible panel elements only in white.

All visible edges seamlessly coated with laser edgeband.

Corners and edges are round with a radius of 3 mm.

Hinges

Lockers 01 and PS have three, all other types two heavy-duty hinges per door.

Alternatively all types can be equipped with a self-closing mechanism starting at a closing angle of 25°.

Locks

Cam lock with master key system. Coin retain, coin return and ticket operated locks or a combination of these different types are available on request.

Interiors

Types 01, 02 and PS with turnable nylon triple hook. Type 01 and PS have an additional hat rack. Type PS 470 with movable partition wall. All doors with aluminium number plates, numbering at choice. Key tags, bracelets and coat hangers on request.

Plinth frames

Made of aluminium profiles, 40 mm diameter, height 150 mm or 500 mm, with heavy-duty nylon rosettes, height-adjustable. Plinths with protruding benches are alternatively available.

Following colours are available without surcharge

Carcass: white.

Doors and sidewalls: 12 standard colours without surcharge and 18 special colours at extra cost.

Triple hook: white.

Nylon rosettes: 7 colours.

Plinth frames: anodized or powder-coated in 7 colours.

Environmental Protection

We do not use materials containing PVC or asbestos.

Suitable for normal use in dry areas.

