

TECHNICAL DETAILS

Design 13 RS (Wet area)

This type is TÜV-certified and has the GS mark (tested for safety).

Height

2022 mm with 150 mm ground clearance, headroom 1985 mm
2162 mm with 150 mm ground clearance, headroom 2125 mm

Front walls

13 mm water resistant HPL-Panels with coarse matt surface on both sides. All visible edges milled and bevelled. An aluminium cover rail, 37 x 29 mm, which runs over the entire front, guarantees high stability. Wall connections with square aluminium-U-profiles 17 x 30 mm.

Doors

Same material as front walls, self closing. All visible edges milled and bevelled in 1 mm radius and all corners are rounded off in 3 mm radius. Square aluminium door stop profile 37x 25,6 mm. Rubber seal on lock side for silent closing.

Partitions

Same material as front walls. All visible edges milled and bevelled. Wall and front connections with square aluminium-U-profiles 17 x 30 mm.

Support Legs

Powder-coated aluminium profiles, 20 mm diameter, with heavy-duty nylon rosettes, height-adjustable, concealed fixing to the floor, inserted into vertical profiles.

Hardware

Each door with 3 triple knuckle stainless steel hinges with brass axle, thereof one spring hinge. Either polished or powder-coated in 7 colours without surcharge. Delta-Tone and Delta-Seal coating protect the spring inside the hinge from corrosion. Powder-coated aluminium lock case with stainless steel latch and turn button with red/white indicator with emergency opening on the outside.

Accessories

Each cubicle with 1 nylon coat hook and a door buffer. Concealed fixing.

Profiles and support angles

Anodized or powder-coated, available in 7 colours without surcharge.

Colours for panels

12 standard colours without surcharge and 18 special colours at extra cost.

Colours for nylon parts

7 colours available without surcharge.

Privacy Screens wall mounted

400 x 900 mm
Wall connection with 2 aluminium support angles. Front corners with 100 mm radius.

13 mm version: same material as front walls.

Glass version: consisting of 2 pieces of glass with a matt foil in between. Wall connection with 4 stainless steel support angles.

Privacy Screens floor mounted

500 x 1850 mm
Same material as front walls. Wall connection with 2 aluminium support angles. Bottom of the screen fixed with support leg.

Environmental Protection

We do not use materials containing PVC or asbestos.

Suitable for high demands in wet areas.

